



# New GPT HAND TOOL RANGE

# professional

Robust-

Rev SCISSORS SCREWDRIVERS SOCKETS & WRENCHES SOCKETS & WRENCHES PLIERS, NIPPERS & WRENCHES TOOL HOLDERS & KITS SPANNERS & HAMMERS SPANNERS & HAMMERS CUTTERS, SAWS & FILES TAPES, LEVELS & LINES

> For every professional, using quality tools specific for each job is essential; Cembre, always attentive to the needs of the electrical sector, has developed a new range of hand tools made specifically to meet the needs of the commercial and industrial installer.

# Professional SCISSORS







#### **Professional Scissors SC5X**

#### Main Features

		Dimensions mm		
Model	Length	Width	Height	Weight g
SC5X	162	77	18	121

Professional scissors with **Special Steel frame** for high resistance and long life. Ergonomic and dual compound plastic handles: structure in Polyamide loaded with Glass fibre and inserts of soft Rubber.

The anti-loosening pivot and bevelled profile allow the accurate and consistent alignment of the blades.

High hardness blades (58 HRC) and an anti-slip serrated edge for making precise cuts even on more difficult materials.

Shaped groove for cutting conductor up to 50 mm<sup>2</sup>.

Supplied with carry case and swivel belt hook.



## Professional Scissors SC3X

Main Features				
		Dimensions mm	1	
Model	Length	Width	Height	Weight g
SC3X	150	75	20	86

Professional scissors with a serrated blade and dual-compound plastic handles with hand protection.

The anti-loosening pivot and bevelled profile allow the accurate and consistent alignment of the blades required for perfect cuts and stripping.

The high hardness of the blades (56HRC) and with their shaped grooves ensure the cutting of flexible conductors up to 35 mm<sup>2</sup>.



## **Professional Scissors SC1**

. .

Main Features				
		Dimensions mm		
Model	Length	Width	Height	Weight g
SC1	145	76	17	78

Professional scissors with ergonomic and dual-compound plastic handles. High tensile steel blades allowing for excellent strength and performance. Provided with specially micro-serrated blades and a robust pivot.

() Cembre 3

# Professional SCREWDRIVERS

The Cembre range of insulated screwdrivers have dual compound handgrips and an ergonomic design making them particularly practical and comfortable in the following modes of use: Each individual screwdriver is tested in accordance with EN 60900

Soft and durable hand

A 1000V 13 O'E

guard



Blade type identification on

the back of the handle

NormalFastForced

To ensure quick identification, the type and size of the head are indicated in different colours on the back of the handle.

The heads are made from Chromium Molybdenum steel with a hardness of 55-59 HRC and are hardened with Phosphoric Manganese Acid to increase corrosion resistance; the size of the insulating cover allows it to be inserted into tight spaces.

> Narrow insulating cover to allow insertion into tight spaces

Chromium Molybdenum steel head with hardness 55-59 HRC and anticorrosion surface treatment

Shaped blade for greater resistance and stability

Ergonomic and shaped hand grip

Coating in dual compound plastic material with soft rubber inserts

Head type identification codes: • **White** - Flat head

- Yellow "Phillips" cross head
- Green "Pozidriv" cross head
- **Red** "Phillips" combination head
- Blue "Pozidriv" combination head

Steel tips

4





A 1218

Hand guard



Attachment hole

# Professional SCREWDRIVERS



## Flat head screwdrivers

Main Features					
	Head Dimensions mm		Blade	Total	Weight g
Model	Width	Thickness	Length mm	Length mm	weight g
SDC 3 X 100-KV	3	0,5	100	185	32
SDC 3.5 X 100-KV	3,5	0,6	100	185	35
SDC 4 X 100-KV	4	0,8	100	205	58
SDC 5.5 X 125-KV	5,5	1,0	125	230	78
SDC 6.5 X 150-KV	6,5	1,2	150	265	115
SDC 8 X 175-KV	8	1,2	175	298	181

## PH Phillips cross head screwdrivers

Main Features				
	Head Dime	ensions mm	Total	Maight g
Model	Size	Blade Length	Length mm	Weight g
SDC 0PH-KV	PH0	60	145	29
SDC 1PH-KV	PH1	80	188	64
SDC 2PH-KV	PH2	100	215	94

#### PZ Pozidriv cross head screwdrivers



0

 $\bigcirc$ 

Main Features

	Head Dim	ensions mm	Total	Mainht a
Model	Size	Blade Length	Length mm	Weight g
SDC 0PZ-KV	PZ0	60	145	29
SDC 1PZ-KV	PZ1	80	188	64
SDC 2PZ-KV	PZ2	100	215	94

# PHSL Phillips combination head screwdrivers

Main Features

	Head Dime	ensions mm	Total	14/-:
Model	Size	Blade Length	Length mm	Weight g
SDC 1PH-SL-KV	PH1 SL	80	188	65
SDC 2PH-SL-KV	PH2 SL	100	215	94

## PZSL Pozidriv combination head screwdrivers 😴

Main Features
---------------


	Head Dim	Head Dimensions mm		14/=:=====	
Model	Size	Blade Length	Length mm	Weight g	
SDC 1PZ-SL-KV	PZ1 SL	80	188	65	
SDC 2PZ-SL-KV	PZ2 SL	100	215	94	

## Set of 7 Screwdrivers - KSDC 7 KV



Main Features				
Set consists of:	Dimens	ions mm	Total	Maight g
Model	Head Size	Blade Length	Length mm	Weight g
SDC 3 X 100-KV	3	100	185	32
SDC 4 X 100-KV	4	100	205	58
SDC 5,5 X 125-KV	5,5	125	230	78
SDC 6,5 X 150-KV	6,5	150	265	115
SDC 0PH-KV	PH0	60	145	29
SDC 1PH-KV	PH1	80	188	64
SDC 2PH-KV	PH2	100	215	94





A fully functioning flat head screwdriver with a completely transparent handle allowing visibility of the indicator from any angle, ensuring high safety.

- Transparent handleHigh quality head
- Ergonomic design
- Pocket clip with spring




## Screwdriver with 45° angled flat head

Main Features					
	Head Dime	ensions mm	Blade	Total	Mainht a
Model	Size	Thickness	length mm	Length mm	Weight g
SDC 2.5 X 55 B	2,5	0,55	55	143	28
SDC 3.5 X 55 B	3,5	0,55	55	143	29

Screwdriver with angled head, ideal for terminals, sensors and actuators.

$\bigcirc$	Flat head stubby screwdriver					
Main Features						
	Head Dimensions mm		Blade	Total	M. 1. L. L.	
Model	Size	Thickness	length mm	Length mm	Weight g	
SDCS 2.5 X 55	5,5	2,5	25	75	37	







# Professional HEX SOCKET SCREWDRIVERS

models and features





## Universal key for switchboards UKC4

Main Features				
		Dimensions mm		_
Model	Length	Width	Height	Weight g
UKC4	72	72	14	92
Universal key for switchboards Equipped with: Triangular shape 7-8 mm				

Equipped with: Triangular shape 7-8 mm Double notch 3-5 mm Square shape 5-6, 7-8 mm Screwdriver bit and hexagonal holder

# Professional **PLIERS**



() Cembre

# Professional PLIERS, NIPPERS & WRENCHES



	Total	Head Dime	14/=:=====	
Model	Length mm	Width	Thickness	Weight g
UPC 180-KV	180	27	11	287
UPC 200-KV	200	32	11,6	381

## TR Nippers

Main Features				
	Total	Head Dime	ensions mm	M. 1. 1. 1
Model	Length mm	Width	Thickness	Weight g
TR 160-KV	160	19	10	229

#### TR Heavy duty nippers

Main Features				
	Total	Head Dime	ensions mm	Woight a
Model	Length mm	Width	Thickness	Weight g
TR 200-KV	200	30	13	306

## SPC Straight nose pliers

Main Features				
	Total	Head Dim	ensions mm	Malahta
Model	Length mm	Width	Thickness	Weight g
SPC 200-KV	200	21,5	10,7	257

#### SPC 45° nose pliers

Main Features				
	Total	Head Dime	ensions mm	Mainht a
Model	Length mm	Width	Thickness	Weight g
SPC 200B-KV	200	21,5	10,7	261

#### WPC Pipe wrench

Main Features				
	Total	Head Dime	ensions mm	Mainht a
Model	Length mm	Width	Thickness	Weight g
WPC 250-KV	250	29	7,7	380

111

Cembre offers a range of tool holders designed to provide professional users with practical and neat ways to optimise their time and working conditions.

## SOFT Line

# Dimensions mm Weight kg Model Length Width Height CTSB 1 420 250 340 3

Practical tool bag in robust fabric, with 2 separate compartments to neatly arrange hand tools. Additional equipment may be accommodated via handy hooks and external pockets while documents are safely stored inside. A shoulder strap and sturdy metal handle make it easy to carry.

# SOFT Line



## Bag Kit CTSB1-1

Ma	1 an 1	<b>F</b> -	- 1.	
1110		10	uu	11 C

	Dimensions mm			Kit Weight	
Model	Length	Width	Height	kg	
KIT CTSB 1-1	420	250	340	5,6	

CTSB 1 equipped with selection of tools.

## Tools contained in the kit:

Qty	item	description
1	SDC3X60-PD	mains tester
1	SDC3X100-KV	screwdriver 3x100
1	SDC3.5X100-KV	screwdriver 3,5x100
1	SDC4X100-KV	screwdriver 4x100
1	SDC5.5X125-KV	screwdriver 5,5x125
1	SDC1PH-KV	screwdriver ph1
1	SDC2PH-KV	screwdriver ph2
1	SDC1PZ-KV	screwdriver pz1
1	SDC2PZ-KV	screwdriver pz2
1	UPC180-KV	pliers 180 mm
1	SC5X	scissors SC5X
1	FLS 3	measuring tape 3m
1	KAK9	allen keys
1	HB18	retractable cutter
1	HKS6	pocket hacksaw
1	LVL150	level 150 mm
1	HMR 300	hammer



## Bag Kit CTSB1-3

Main Features				
		Dimensions mm		Kit Weight
Model	Length	Width	Height	kg
KIT CTSB 1-3	420	250	340	6,8

CTSB 1 equipped with selection of tools.

#### Tools contained in the kit:

Qty	item	description
1	SDC3X60-PD	mains tester
1	SDC3X100-KV	screwdriver 3x100
1	SDC3.5X100-KV	screwdriver 3,5x100
1	SDC4X100-KV	screwdriver 4x100
1	SDC5.5X125-KV	screwdriver 5,5x125
1	SDC1PH-KV	screwdriver ph1
1	SDC2PH-KV	screwdriver ph2
1	SDC1PZ-KV	screwdriver pz1
1	SDC2PZ-KV	screwdriver pz2
1	UPC180-KV	pliers 180 mm
1	TR160-KV	nippers 160 mm
1	SC5X	scissors SC5X
1	PTS4	wire stripper 0.2-6 mm <sup>2</sup>
1	FLS 5	measuring tape 5 m
1	KAK9	allen keys
1	KRK4	spanners with ratchet
1	UKC4	universal key
1	HB18	retractable cutter
1	HKS6	pocket hacksaw
1	LVL150	level 150 mm
1	HMR 300	hammer

# Professional TOOL HOLDERS

# HARD Line

		Case VAL GPTA				
Main Features						
		Dimensions mm				
Model	Length	Width	Height	weight kg		
VAL GPTA	470	360	185	4,8		

Aluminium case containing two panels with elastic tool holders and an internal pocket for holding documents or a tablet. Thermoformed base with modular dividers. Fitted with an ergonomic carrying handle and a hinged lid with stop to limit the opening to 90°.



# HARD Line



## Case Kit VAL GPTA-1

Main Features				
	Dimensions mm			
Model	Length	Width	Height	kg
KIT VAL GPTA-1	470	360	185	7,4

Case VAL GPTA equipped with selection of tools.

#### Tools contained in the kit:

Qty	item	description
1	SDC3X60-PD	mains tester
1	SDC3X100-KV	screwdriver 3x100
1	SDC3.5X100-KV	screwdriver 3,5x100
1	SDC4X100-KV	screwdriver 4x100
1	SDC5.5X125-KV	screwdriver 5,5x125
1	SDC1PH-KV	screwdriver ph1
1	SDC2PH-KV	screwdriver ph2
1	SDC1PZ-KV	screwdriver pz1
1	SDC2PZ-KV	screwdriver pz2
1	UPC180-KV	pliers 180 mm
1	SC5X	scissors SC5X
1	FLS 3	measuring tape 3m
1	KAK9	allen keys
1	HB18	cutter
1	HKS6	pocket hacksaw
1	LVL150	level 150 mm
1	HMR 300	hammer



Main Features				
		Dimensions mm		_ Kit Weight
Model	Length	Width	Height	kg
KIT VAL GPTA-2	470	360	185	9,6

Case VAL GPTA equipped with selection of tools.

#### Tools contained in the kit:

	1.	1
Qty	item	description
1	SDC3X60-PD	mains tester
1	SDC3X100-KV	screwdriver 3x100
1	SDC3.5X100-KV	screwdriver 3,5x100
1	SDC4X100-KV	screwdriver 4x100
1	SDC5.5X125-KV	screwdriver 5,5x125
1	SDC1PH-KV	screwdriver ph1
1	SDC2PH-KV	screwdriver ph2
1	SDC1PZ-KV	screwdriver pz1
1	SDC2PZ-KV	screwdriver pz2
1	UPC180-KV	pliers 180 mm
1	TR160-KV	nippers 160 mm
1	SC5X	scissors SC5X
1	PTS4	wire stripper 0.2-6 mm <sup>2</sup>
1	FLS 5	measuring tape 5 m
1	KAK9	allen keys
1	KRK4	spanners with ratchet
1	UKC4	universal key
1	HB18	retractable cutter
1	HKS6	pocket hacksaw
1	LVL150	level 150 mm
1	HMR 300	hammer

# Professional TOOL HOLDERS

() Cembr

(O combro)

	Chest VAL GPT				
Main Features					
		Dimensions mm			
Model	Length	Width	Height	- Weight kg	
VAL GPT	557	230	245	3,7	

Plastic tool chest with small parts holder on the lid; Removable internal tool tray. Metal latches; Aluminium handle and padlock facility. Sufficiently robust to be used as a step when closed. Stackable with other VAL GPT tool chests.

# HARD Line



Main Features				
		Dimensions mm	1	Chest Kit
Model	Length	Width	Height	Weight kg
KIT VAL GPT-1	557	230	245	5,48

VAL GPT equipped with selection of tools

#### Tools contained in the kit:

Qty	item	description
1	SDC3X60-PD	mains tester
1	SDC3X100-KV	screwdriver 3x100
1	SDC4X100-KV	screwdriver 4x100
1	SDC5.5X125-KV	screwdriver 5,5x125
1	SDC6.5X150-KV	screwdriver 6,5x150
1	SDC1PH-KV	screwdriver ph1
1	SDC2PH-KV	screwdriver ph2
1	TR160KV	nippers 160mm
1	SC5X	scissors SC5X
1	FLS 3	measuring tape 3m
1	HB18	cutter
1	HKS6	pocket hacksaw
1	LVL150	level 150 mm
1	HMR 300	hammer

# Professional **TOOL HOLDERS**

## Pouch

#### Pouch CTBB1

	Frat was	
iviain	Features	

		Dimensions mm		14/=:=!++ =
Model	Length	Width	Height	- Weight g
CTBB 1	230	150	50	84

Made from soft and strong fabric, equipped with a fast stud belt fastening. It has handy preformed compartments for holding pliers, scissors and screwdrivers.



## Pouch Kit CTBB1-1

	Dimensions mm			Pouch Kit	
Model	Length	Weight g			
KIT CTBB 1-1	230	150	50	477	

CTBB1 equipped with selection of tools.

#### Tools contained in the kit:

Qty	item	description
1	SDC3X100-KV	screwdriver 3x100
1	SDC3.5X100-KV	screwdriver 3,5x100
1	SDC4X100-KV	screwdriver 4x100
1	SDC1PH-KV	screwdriver ph1
1	SDC2PH-KV	screwdriver ph2
1	SC5X	scissors SC5X



models and features

in Features	5						
	$\bigcirc$	Open	Ring	Open thick-	Ring thick-	Total	weight
del	mm	width mm	width mm	ness mm	ness mm	Length mm	g
/60	6	16	10	4	5	110	15
/70	7	17	11	4	5	120	19
/80	8	19	13	4	6	130	24
/100	10	23	16	5	7	150	35
/110	11	26	17	5	7	160	47
/130	13	30	20	6	8	180	68
/140	14	32	21	6	9	190	79
/150	15	34	23	6	10	200	89
/170	17	37	26	7	10	220	124
				the second se		the second se	

#### **CW Combination Spanners**

	$\bigcirc$	Open	Ring	Open thick-	Ring thick-	Total	weight
Model	mm	width mm	width mm	ness mm	ness mm	Length mm	ğ
CW60	6	16	10	4	5	110	15
CW70	7	17	11	4	5	120	19
CW80	8	19	13	4	6	130	24
CW100	10	23	16	5	7	150	35
CW110	11	26	17	5	7	160	47
CW130	13	30	20	6	8	180	68
CW140	14	32	21	6	9	190	79
CW150	15	34	23	6	10	200	89
CW170	17	37	26	7	10	220	124
CW180	18	39	27	7	11	230	149
CW190	19	41	28	7	11	240	166
CW220	22	47	32	8	13	270	227
CW240	24	51	35	8	14	290	293
CW270	27	56	39	9	15	320	374
CW300	30	62	43	10	15	350	475
CW320	32	66	46	10	16	370	580

• Chromium-vanadium steel tools

• Satin chrome finish.

Ma

- Ring head with 12 grip points, offset with respect to the handle on the second second



#### KCW12 Combination Spanner Set

Main Features					
	Dimensions KIT mm				
Model	Length	Width	Height	weight g	
KCW12	460	362	65	1140	

#### Set includes:

#### KCW12:

CW60 - CW70 - CW80 - CW100 - CW110 CW130 - CW140 - CW150 - CW170 - CW180 - CW190 - CW220





# Professional HAND TOOLS



## Combination spanners with jointed ratchet head KRK 4

Main Features

	Kit Dimensions mm				
Model	Length	Width	Height	Weight g	
KRK 4	335	190	18	390	

• Sizes included: 8-10-13-17 mm

• Chromium-vanadium steel

• 180° swivel head

• Ratchet mechanism with 72 teeth and recovery angle of 5°.

## Socket set 1/4" drive KRS47

Main I	eature	2
--------	--------	---

	Dimensions KIT mm				
Model	Length	Width	Height	- Weight g	
KRS47	285	136	44	1655	

• Standards: UNI ISO 3315 - DIN 3122

#### Metal case contains:

Qty	description
1	reversible ratchet wrench with socket retention system
2	extensions
1	articulated joint
1	T bar with sliding handle
1	screwdriver style holder
13	sockets 4 to 14 mm
4	extended sockets 8 to 13 mm
3	screwdriver sockets 4 to 6.5 mm
3	screwdriver sockets PH1, PH2, PH3
3	screwdriver sockets PZ1, PZ2, PZ3
6	hex socket spanners 3 to 8 mm
3	hex Allen keys 1.5 to 5 mm
6	torx socket keys T10 to T40
	•

#### Adjustable wrench AWC300

#### Main Features

	Dimensions mm			
Model	Max Opening	Length	Width	Weight g
AWC300	34	300	-	620

• Chromium-vanadium steel wrench

Phosphate finish

• Equipped with rapid adjustment and gap size measurement scale

• Wide-opening jaws for greater adaptability

#### Set of 9 male Allen keys KAK 9

#### Main Features

	K	Kit Dimensions mm			
Model	Length	Width	Height	Weight g	
KAK 9	300	100	31	430	

- Sizes included: 1.5-2-2.5-3-4-5-6-8-10 mm
- Chromium-vanadium steel
- Long reach type
- Spherical head for use up to 30°
- Equipped with carrying case



(i) e



C arrest

#### Deep hexagonal sockets ½" drive DSC

$\square$		Dimensions mm		
mm	Length	Ø Ext. hexagon	Ø Ext. drive	Weight g
17	77	23,8	22	120
19	77	25,7	24	134
24	77	31,8	27,8	210
30	77	39,9	34	300
32	77	41,8	35,8	336
	17 19 24 30	17         77           19         77           24         77           30         77	Length         Ø Ext. hexagon           17         77         23,8           19         77         25,7           24         77         31,8           30         77         39,9	Length         Ø Ext. hexagon         Ø Ext. drive           17         77         23,8         22           19         77         25,7         24           24         77         31,8         27,8           30         77         39,9         34


• Chromium-vanadium steel

Satin chrome finish

• Standards: UNI ISO 2725 - DIN 3124



1/2" Reversible ratchet wrench CRH12



• Mechanism with 72 teeth and a recovery angle of 5°

- Reversible ratchet system
- Ergonomic handle in dual compound material
- Satin chrome finish
- Chromium-vanadium steel
- Standards: UNI ISO 3315 DIN 3122

#### 1/2" Drive extension 250 mm long EBC12-250

Main Features							
Model	Length mm	Weight g					
EBC12-250	250	441					
Socket quick release system     Chromium-vanadium steel     Satin chrome finish     Standards: UNI ISO 3316 - DIN 3123							



#### 1/2" Drive T bar with sliding handle STBC12.300



# Professional HAMMMERS & REMOVAL TOOLS



#### Hammer HMR 300

#### Main Features

	Dimensions mm					
Model	Length	Width	Height	Weight g		
HMR 300	300	104	23	300		

300 g bench hammer with patented anti-vibration triple compound handle. Aluminium alloy 6082 T6 P-Al Si 1 Mg Mn head. External surface of the handle in Polyamide A2800. Thermoplastic rubber grip. Complete with handle sleeve.

#### Hammer HMR 500W

wain Features				
		_		
Model	Length	Width	Height	Weight g
HMR 500W	320	106	27	500

500 g bench hammer with Ash handle. Complete with handle sleeve.

Main Fosturos

#### Chisel with hand protector BLC250

Model	5	Blade width			5 5
BLC250	250	23	16	34	492


23 mm Chromium-vanadium steel blade with sturdy thermoplastic hand protector

#### Centre Punch CPC100-8

Main Features							
	Dimensions mm						
Model	Length	Tip	Hexagon	Weight g			
CPC100-8	100	3	8	54			

Chromium-vanadium steel with Chrome finish

#### Crowbar CPW 500



Hexagonal section C40 steel

in Features				
Madal		Dimensions mr Width		Weight g
Model HB 18	Length	32	Height <b>17</b>	Weight g 223
Replaceable blade, adju Steel blade, metal hand Safety lock for blade.	stable from 18 mrr lle, with soft Rubbe	n and internal er anti-slip coa	l autoloader w ating.	ith 5 blades.
		Ha	cksaw H	KS 12
Main Features				
Model	Length	Dimensions mm Width	n Height	Weight g
HKS 12	400	140	32	600
Main Features		H	lacksaw l	HKS 6
		Dimensions mm		147 - 17
Model HKS 6	Length 270	Width 115	Height <b>20</b>	Weight g 215
Hacksaw with 150 mm the blade.		·		
Soft Rubber anti-slip ha			ade BL1	2 HKS
			ade BL1	2 HKS
Soft Rubber anti-slip ha	e for <b>HKS12</b> (5 pie for <b>HKS6</b> (10 piec	eces) Eces)	ade BL1; Blade BL( 200 - RF	6 HKS
Soft Rubber anti-slip hai BL12 HKS Spare blad	e for <b>HKS12</b> (5 pie for <b>HKS6</b> (10 piec <b>Fi</b>	eces) Tes)	Blade BL( 200 - RF	6 HKS
Soft Rubber anti-slip hai BL12 HKS Spare blad BL6 HKS Spare blade	e for <b>HKS12</b> (5 pie for <b>HKS6</b> (10 piec <b>Fi</b> File Fi	eces) res) les SFC	<b>Blade BL</b> <b>200 - RF</b> 'e Total	6 HKS C200
Soft Rubber anti-slip hai BL12 HKS Spare blad	e for <b>HKS12</b> (5 pie for <b>HKS6</b> (10 piec <b>Fi</b> <i>File Fi</i> <i>Section mm Lengt</i>	eces) res) les SFC	Blade BL( 200 - RF 'e Total mm Length mm	6 HKS
Soft Rubber anti-slip hai BL12 HKS Spare blad BL6 HKS Spare blade Second-cut square file SFC200	for <b>HKS12</b> (5 pie for <b>HKS6</b> (10 piec File Fi Section mm Lengt <b>8 20</b> File Fi	eces) Iles SFC	Blade BL 200 - RF e Total mm Length mm 310 e Total	6 HKS
Soft Rubber anti-slip hai BL12 HKS Spare blad BL6 HKS Spare blade Second-cut square file SFC200 Second-cut round file	for <b>HKS12</b> (5 pie for <b>HKS6</b> (10 piec File Fi Section mm Lengt <b>8 20</b> File Fi Sengtine Fi diam. mm Lengt	eces)  Iles SFC ile handl h mm Length n 00 110 ile handl h mm Length r	Blade BL( 200 - RF 'e Total mm Length mm ) 310 'e Total mm Length mm	6 HKS
Soft Rubber anti-slip hai BL12 HKS Spare blad BL6 HKS Spare blade Second-cut square file SFC200 Second-cut round file RFC200	for <b>HKS12</b> (5 pie for <b>HKS6</b> (10 piec File Fi Section mm Lengt <b>8 20</b> File Fi	eces)  Iles SFC ile handl h mm Length n 00 110 ile handl h mm Length r	Blade BL( 200 - RF 'e Total mm Length mm ) 310 'e Total mm Length mm	6 HKS
Soft Rubber anti-slip hai BL12 HKS Spare blad BL6 HKS Spare blade Second-cut square file SFC200 Second-cut round file	for <b>HKS12</b> (5 pie for <b>HKS6</b> (10 piec File Fi Section mm Lengt <b>8 20</b> File Fi Sengtine Fi diam. mm Lengt	eces)  Iles SFC ile handl h mm Length n 00 110 ile handl h mm Length r	Blade BL( 200 - RF 'e Total mm Length mm ) 310 'e Total mm Length mm	6 HKS
oft Rubber anti-slip hai BL12 HKS Spare blad BL6 HKS Spare blade Second-cut square file SFC200 Second-cut round file RFC200 Carbide steel	for <b>HKS12</b> (5 pie for <b>HKS6</b> (10 piec File Fi Section mm Lengt <b>8 20</b> File Fi Sengtine Fi diam. mm Lengt	eces)  Iles SFC ile handl h mm Length n 00 110 ile handl h mm Length r	Blade BL( 200 - RF 'e Total mm Length mm ) 310 'e Total mm Length mm	6 HKS C200 Weight g 108 Weight g

5 m **19 mm** 83x71x36

Weight g

166

252



#### Measuring tapes FLS3 - FLS5

Main Features			
	Tape din	Casing	
Model	Length	Width	Dimensions mm
FLS3	3 m	16 mm	71x62x33

Professional measuring tapes with ergonomic hand grip, metal casing and rubber inserts. Tape coating in Polyamide to ensures durability, anti-friction and resistance to corrosion; with integrated magnetic hook.

Automatic lock and dual locking button.

Ма

FLS5

## Spirit Levels LVL150 - LVL200 - LVL400

Main Features					
	Dimensi	ons mm		M. 1. L. C.	
Model	Length	Width	<ul> <li>No. of tubes</li> </ul>	Weight g	
LVL150	150	22	2	105	
LVL200	200	22	2	157	
LVL400	400	22	2	248	

Made from robust Aluminium profile, with precision 0.5 to 1 mm. Shock resistant tubes and high absorption protective caps.





#### Chalk line PWT 1

Main Features				
	String	Chalk	Chalk	Weight Kit
Model	length	quantity	colour	g
PWT 1	30 m	113 g	Blue	334

Made from dual compound material, with shock proof protection.

Wind and lock the string by the crank.

String equipped with toothed attachment.

113 g of blue chalk in a refillable container.

## Chalk refill for chalk line PWS 150 B

**PWS 150B** colour blue – Quantity 200 g

## CONICAL STEPPED DRILL-BITS

	Co	nica	steppe	d drill-l	bit SC	-PG1
Main Features						
	Hole Ø range		Steps	Drill s	ize mm	_
Model	mm	N°	Height mm	Length	Stem Ø	Weight g
SC-PG1	6 - 37	12	2	100	10	293
Step angle 90			Clasranca	or		
Step	Hole Ø mn	n	Clearance f PG thread	or		
1	6.0		-			
2	9.0		-			-
3	12.5		7		6	
4	15.2		9			
5	18.6		11			
6	20.4		13.5			
7	22.5		16			
8	26.0		-			
9	28.3		21			
10	30.5		-			
11	34.0		-			
12	37.0		29			

## Conical stepped drill-bit SC-M1

Main Featur	es						
	Hole Ø range		Steps	Drill s	ize mm		
Model	mm	N°	Height mm	Length	Ø Stem	Weight g	
SC-M1	6.5 - 40.5	11	2	96	10	303	
<ul> <li>Point geom</li> <li>No pre-dril.</li> <li>Step angle</li> <li>SC-M1 - Hol</li> </ul>	90°	DIN 14	12 C				-TIBOT
Step	Hole Ø mm		Clearance f Metric thre			2	
1	6.5		-			-	
2	8.5		-				
3	10.5		-				

- Point geometry according to DIN 1412 C
- No pre-drilling
  Step angle 90°

#### SC-M1 - Hole Sizes:

Step	Hole Ø mm	Clearance for Metric thread
1	6.5	-
2	8.5	-
3	10.5	-
4	12.5	M12
5	16.5	M16
6	20.5	M20
7	25.5	M25
8	29.0	-
9	32.5	M32
10	36.5	-
11	40.5	M40

## SPIRAL DRILL-BITS SB7-SDS-PLUS, SB-19, SB19-TIN

#### Set of 7 Hammer Drill-Bits SB7-SDS-PLUS

Main Features

Model

SB7-SDS-PLUS

Drill-bits with a strengthened core, to allow optimum force transmission from start to finish. Made from steel worked at a low temperature to achieve maximum resistance, and created with a spiral structure for efficient waste extraction during opeartion.

Spiral Drill-bits SB19: Spiral Drill-bits SB19-TIN:

Suitable for rock, brick work, concrete, cement, granite, tiles and marble. Fits all hammer drills with SDS-Plus and Hilti TE 10 double-groove shanks. Corresponding to standard: ISO 5468-DIN 8039. Weight 752 g.

Hammer	Dril	l-bits	SB7	-SDS	PLU	JS:

Ø	Length mm	
mm	total	useable
5	110	50
6	110	50
6	160	100
8	110	50
8	160	100
10	160	100
12	160	100

### SB19-TIN

Sets of 19 Spiral Drill-Bits SB19

SB19

SB7-SDS-PLUS

Main	Features

# Model

## SB19

High speed, high performance, steel spiral drill-bits. Cross-wise sharpening allows for good balance, reducing strain during the operation. Spiral angle: 25-30° Groove profile: standard Core: standard Back angle: 118° Point geometry: Shape C Weight: 675 g Main use: Steel N/mm<sup>2</sup> <900, Cast iron Secondary use: Steel N/mm<sup>2</sup> <1100, Stainless steel, Alluminium, Brass, Bronze.

#### Model SB19-TIN

As type SB19 with additional: TiN coating to increase operating life by 300 - 400%

ø	Length mm	
mm	total	useable
1	34	12
1,5	40	18
2	49	24
2,5	57	30
3	61	33
3,5	70	39
4	75	43
4,5	80	47
5	86	52
5,5	93	57
6	93	57
6,5	101	63
7	109	69
7,5	109	69
8	117	75
8,5	117	75
9	125	81
9,5	125	81
10	133	87







Cembre S.p.A. Telefono: +39 030 36921 Telefax: +39 030 3365766 www.cembre.it E-mail: sales@cembre.com



**Cembre Ltd.** Tel.: 01675 470440 Fax: 01675 470220 www.cembre.co.uk E-mail: sales@cembre.co.uk





Cembre España S.L. Teléfono: 91 4852580 Telefax: 91 4852581 Telefax: 47) 33361765 Telefax: 47) 33361766 www.cembre.as E-mail: comercial@cembre.as



Cembre GmbH Telefon: 089/3580676 Telefax: 089/35806777 www.cembre.de E-mail: sales@cembre.de



www.cembreinc.com E-mail: Sales.US@cembreinc.com

Any other country, please contact Cembre S.p.A. - Italy

